

Approved Body No. 1121

Certificate of Constancy of Performance 1121-CPR-UK-AE7613

In compliance with Construction Products Regulation 2011 (retained EU law EUR 2011/305) as amended by the Construction Products (Amendment etc.) (EU Exit) Regulations 2019 and the Construction Products (Amendment etc.) (EU Exit) Regulations 2020, this certificate applies to the Construction Product:

(the Construction Products Regulation or CPR), this certificate applies to the construction product

Briton 2130B.TE.C, Briton 2130B.TE.L & Briton 2130B.TE.S Overhead door closer (Size 3 to 4)

Intended use:- For use on fire rated single leaf and double leaf doors STANDARD DOOR MOUNT PULL SIDE FIXING APPLICATION.

Essential characteristics	Performance	Designated Standard
Test Mechanical Ref : 636PCT, 135129 & WIL 428092		
Fire Test Evidence : WF 141156 lss 3 / 148518 WF 148519 / WF 417359 / WF 417360 lss 3 & WF No 422918 lss 2		
Ability to release		
5.1.2 release from any angle	Pass	
5.1.3 Not possible to inhibit the release	Pass	
5.1.4 Supply voltage	Pass	
5.1.5 External electrical connection	Pass	
5.1.6 Inlet for external wiring	Pass	
5.2.1 General	Pass	
5.2.2 Electrical release	Pass	
requirements		EN 1155:1997+A1:2002/AC:2006
5.2.4 Durability	Pass	
5.2.5 Angle of hold open	Pass	
5.2.6 Manual release	Pass	
5.2.7 Continuous hold open	Pass	
5.2.8 Overload performance	Pass	
5.2.9 Delayed release	NPD	
5.2.10 Electrical performance	Pass	
5.1.11 Temperature Rise	Pass	
5.1.12 Damage	Pass	
5.1.13 Fire / smoke doors	Grade 1	
Essential characteristics	Performance	Designated Standard
Durability of Ability to release		
5.2.14.1 corrosion	Grade 3 (96 hours)	
5.2.14.2 corrosion	Pass	
Dangerous Substances	If a reference to dangerous substances is	FN 4455 4007 A4 0000/A 0 0000
Annex ZA3	added in the table ZA.1, the following claim is	EN 1155:1997+A1:2002/AC:2006
	suggested: Pass: the materials in the product do not	
	contain or release any dangerous substances in	
	excess of the maximum levels specified in	
	existing European material standards or any	
	national regulations	

EWC-QU-FT-480 (Issue 7)



Notified body No. 1121

Certificate of Constancy of Performance 1121-CPR-UK-AE7613

produced for

Allegion (UK) Ltd 35 Rocky Lane Birmingham West Midlands B6 5RQ United Kingdom

and produced in the manufacturing plant.

V/017

This is coded format, and the information is held by the Notified Body

This certificate attests that all provisions concerning the assessment and verification of constancy of performance and the performances described in Annex ZA of the standard(s)

EN 1155:1997+A1:2002/AC:2006

Under System 1 for the performance set out in this certificate are applied and that the Factory Production Control conducted by the manufacturer is assessed to ensure the constancy of performance of the construction product.

This certificate was first issued on **29/10/2020** and reissued on **11/03/2023** and will remain valid as long as neither the designated standard, the Construction Product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, or unless suspended or withdrawn by the Approved Product Certification Body.

UKCA certificate valid to: 10/03/2026



0087

Paul Duggan Certification Manager

Warringtonfire Testing and Certification Limited Suite 302, The Genesis Centre, Birchwood, Warrington, WA3 7BH, UK

EWC-QU-FT-480 (Issue 7)