## **Declaration of Performance**



## UK CONSTRUCTION PRODUCTS (AMENDMENT ETC) (EU EXIT) REGULATIONS 2020

No. 47458033

1. Unique identification code of the product-type:

Briton 377, 377D.

Accessories: - 378DDS, 376MDS, 378MDS Briton 1413/LE & 1413/KE, 1413.LE & 1413.KE & 1413.BP.

Briton 9260 Codelock.

2 Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the UK CPR:

Briton 377, 377D.

3. Intended use or uses of the construction product, in accordance with the applicable designated technical specification, as foreseen by the manufacturer:

For use on fire and smoke compartmentation doors

0

Escape route doors, when fitted in accordance with the manufacturer's fitting instructions.

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Allegion (UK) Limited 35 Rocky Lane Aston Birmingham B6 5RQ

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

N/A

System or systems of assessment and verification of constancy of performance of the construction product as set out in UK CPR, Annex V:

## System 1

7. In case of the declaration of performance concerning a construction product covered by a designated standard:

## EN 1125: 2008

Notified Certification body No.1121 performed the type testing and issued test reports.

Certificate of Constancy of Performance - 1121-CPR-UK- AAA7569

8. UK Technical Assessment:

N/A

9. Declared performance

Essential characteristics	Performance	Designated technical Specification
Clause 4.2.1 Ability to release		
(for doors on escape routes)		EN 1125:2008
Release function	< 1 sec	
Panic exit device mounting	Pass	
Exposed edges and corners	> 0,5 mm	
Double doorset	Pass	
Bar installation	Z < 150 mm from frame stop	
Bar length	> 60% of max door width	
Bar projection	W < 100 mm	
Bar end	Pass	
Operating bar face	> 18 mm	
Test rod	Pass	
Door face gap	> 25 mm	

	Pass
Accessible gap	Pass
Door free movement	Pass
Top vertical bolt	Pass
Keepers	Pass
Keepers dimensions	Door mass ≤ 200 Kg, door height ≤ 2520
Door mass and dimensions	mm, door width ≤ 1320 mm
Outside access device	Pass
	< 80 N with the door unloaded, and < 220
Release forces	N with the door loaded with 1 000 N.
Security requirement	Grade 2
Clause 4.2.1 Durability of ability to	
release against aging and degradation	
(for doors on escape routes)	
Corrosion resistance	Grade 3: 96 h
Temperature range	Operating forces at -10 C° and + 60 C° <
	50% in excess of the operating forces at
	+20 C°
	N/A
Covers for vertical rods	Lubrication every 20 000 cycles
Lubrication	< 50 N
Re-engagement force	Grade 7: 200 000 cycles
Durability	1 000 N
Abuse resistance –Horizontal bar	500 N
Abuse resistance –Vertical rod	< 80 N with the door unloaded, and < 220
Final examination	N with the door loaded with 1 000 N
Clause 4.2.1 Self closing ability C	
(for fire/smoke doors on escape routes)	
Re-engagement force	< 50 N
Clause 4.2.1 Durability of self closing	
ability C against aging and degradation (for fire/smoke doors on escape routes)	
Durability	Grade 7: 200 000 cycles
Re-engagement force	< 50 N
Clause 4.2.1 Resistance to fire E	> JU IN
(integrity) and I (insulation)	
(for fire doors on escape routes)	
Suitability of panic exit devices for use	Grade B: Suitable for use on fire/smoke
on fire resisting doorsets assemblies -	door assemblies
Additional requirements	
Control of Dangerous substances	The materials in the device do not
•	contain or release any dangerous
	substances in excess of the maximum
	levels specified in existing European
	material standards or any national
	regulations.

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. Signed for and on behalf of the manufacturer by:

Chris Crampton

Controller - Unitary EMEIA, Finance and Accounting

C2 Comp

Allegion (UK) Limited 35 Rocky Lane Aston Birmingham B6 5RQ