

Notified Body No. 2812

Certificate of Constancy of Performance

2812-CPR-AE0003

In compliance with *Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011* (the Construction Products Regulation or CPR), this certificate applies to the construction product

Briton 2130B.TE.C Overhead door closer (Size 3 to 4)

Intended use:- For use on fire rated single leaf and double leaf doors STANDARD DOOR MOUNT PULL SIDE FIXING APPLICATION.

Essential characteristicsPerformanceHarmonised tech specificationTest Mechanical Ref : 636PCT, 135129 & WIL 428092 Fire Test Evidence : 141156 & WF No 422918Ability to releaseFire Test Evidence : 141156 & WF No 422918Ability to releasePass5.1.2 release from any anglePass5.1.3 Not possible to inhibit the releasePass5.1.4 Supply voltagePass5.1.5 External electrical connectionPass5.1.6 Inlet for external wiringPass5.2.1 GeneralPass5.2.2 Electrical releasePassPassPass	
Test Mechanical Ref : 636PCT, 135129 & WIL 428092 Fire Test Evidence : 141156 & WF No 422918Ability to release 5.1.2 release from any angle 5.1.3 Not possible to inhibit the release 5.1.4 Supply voltage 5.1.5 External electrical connection 5.1.6 Inlet for external wiringPass Pass Pass Pass5.2.1 General 5.2.2 Electrical releasePass	
Fire Test Evidence : 141156 & WF No 422918Ability to releasePass5.1.2 release from any anglePass5.1.3 Not possible to inhibit the releasePass5.1.4 Supply voltagePass5.1.5 External electrical connectionPass5.1.6 Inlet for external wiringPass5.2.1 GeneralPass5.2.2 Electrical releasePass	
Ability to release5.1.2 release from any angle5.1.3 Not possible to inhibit the release5.1.4 Supply voltage5.1.5 External electrical connection5.1.6 Inlet for external wiring5.2.1 General5.2.2 Electrical releasePass	
5.1.2 release from any anglePass5.1.3 Not possible to inhibit the releasePass5.1.4 Supply voltagePass5.1.5 External electrical connectionPass5.1.6 Inlet for external wiringPass5.2.1 GeneralPass5.2.2 Electrical releasePass	
5.1.3 Not possible to inhibit the releasePass5.1.4 Supply voltage	
5.1.4 Supply voltage5.1.5 External electrical connection5.1.6 Inlet for external wiring5.2.1 General5.2.2 Electrical releasePass	
5.1.5 External electrical connectionPass5.1.6 Inlet for external wiringPass5.2.1 GeneralPass5.2.2 Electrical releasePass	
5.1.6 Inlet for external wiringPass5.2.1 General5.2.2 Electrical releasePass	
Pass 5.2.1 General 5.2.2 Electrical release Pass	
5.2.1 General5.2.2 Electrical releasePass	
5.2.2 Electrical release Pass	
Bass	
requirements EN 1155:1997+A1:200	02/AC:2006
5.2.4 Durability	
5.2.5 Angle of hold open Pass	
5.2.6 Manual release Pass	
5.2.7 Continuous hold open Pass	
5.2.8 Overload performance Pass	
5.2.9 Delayed release Pass	
5.2.10 Electrical performance NPD	
5.1.11 Temperature Rise Pass	
5.1.12 Damage Pass	
5.1.13 Fire / smoke doors Pass	
Grade 1	
Essential characteristics Performance Harmonised tech	hnical
specification	
· · · · ·	
Durability of Ability to release 5.2.14.1 corrosion Grade 3 (96 hours)	
5.2.14.2 corrosion Pass	
Dangerous Substances If a reference to dangerous substances is added in the table ZA 1 the following claim is EN 1155:1997+A1:200	02/10.2006
Annex ZAS	UZ/AC.2000
suggested: Pass: the materials in the hinge do not contain or	
release any dangerous substances in excess of	
the maximum levels specified in existing	
European material standards or any national	
regulations	





Certificate of Constancy of Performance

2812-CPR-AE0003

Placed on the Market under the name of:

Allegion (UK) Ltd 35 Rocky Lane Birmingham West Midlands B6 5RQ United Kingdom

and produced in the manufacturing plant.

V/017

This is coded format, and the information is held by the Notified Body.

This certificate attests that all provisions concerning the assessment and verification of constancy of performance and the performances described in Annex ZA of the standard(s)

EN 1155:1997+A1:2002/AC:2006

Under System 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the constancy of performance of the construction product.

This certificate was first issued on **29/10/2020** and re-issued on **29/03/2023** and will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, or unless suspended or withdrawn by the notified product certification body.

CE Marking certificate valid to: 28/03/2026

ERO Project Reference: ERO 034621 P1746

Paul Duggan Certification Manager

