

**Declaration of Performance**
**CONSTRUCTION PRODUCTS REGULATION 2011  
DECLARATION OF PERFORMANCE**
**No. AL-0000402583**

1. Unique identification code of the product-type:
 

**Briton**  
**4801.304, 4802.304, 4803.304,**  
**Briton**  
**Y4801.304, Y4802.304, Y4803.304,**
  
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:
 

**Briton**  
**4801.304, 4802.304, 4803.304,**  
**Briton**  
**Y4801.304, Y4802.304, Y4803.304,**
  
3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:
 

**For use on fire and smoke compartmentation doors**  
**Or**  
**Escape route doors (For other products such as exit devices)**
  
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):
 

**Allegion (UK) Limited**  
**35 Rocky Lane**  
**Aston**  
**Birmingham**  
**B6 5RQ**
  
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):
 

**N/A**
  
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:
 

**System 1**
  
7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:
 

**EN 1935: 2002/AC:2003**  
**Notified testing laboratory No.2812 performed the type testing and issued test reports.**  
**Certificate of Constancy of Performance - 2812-CPR-AC5075**
  
8. European Technical Assessment:
 

**N/A**
  
9. Declared performance

Essential characteristics	Performance	Harmonised technical specification
<b>Self-closing</b> <b>Initial friction torque (door mass 120 kg)</b> <b>Static load</b> <b>Load deformation</b>	<b>&lt; 4,0 Nm with door mass 120kg</b>  <b>Passed with a displacement under load:</b> <b>-lateral &lt; 4 mm</b> <b>-vertical &lt; 2 mm</b> <b>and a residual displacement after unloading.</b> <b>-lateral &lt; 0,6 mm</b> <b>-vertical &lt; 0,3 mm</b>	<b>EN 1935:2002/AC:2003</b>


<b>Overload</b>  <b>Shear strength</b>  <b>Hinges for use on fire-resistant and/or smoke-controls doors</b>	<b>Passed</b>  <b>Passed with a lateral and vertical deformation under loading &lt;3mm</b> <b>Additional lateral and vertical displacement after unloading &lt; 1 mm</b>  <b>Grade 1: suitable for use on fire/smoke resistant door assemblies.</b> <b>120 Minute Metal doors. (IMM &amp; MM)</b> <b>30 and 60 minute timber and mineral based assemblies (ITT)</b>	
<b>Durability</b>  <b>Families of hinges with common design feature</b>  <b>Corrosion resistance</b>	<b>Passed a 200 000 cycles test with a maximum wear:</b> <b>-lateral &lt; 0,5 mm</b> <b>-vertical &lt; 1,0 mm</b> <b>Maximum frictional torque.</b> <b>-after 20 cycles &lt; 3.0 Nm</b> <b>-after the completion of 200 000 cycles &lt; 3.0 Nm</b>  <b>The hinge covered by this DoP is the hinge tested</b>  <b>Grade 4 Neutral Salt Spray (NSS) : 240 h</b>	
<b>Dangerous substances</b>	<b>Pass: the materials in the hinge do not contain or release any dangerous substances in excess of the maximum levels specified in existing European material standards or any national regulations (1)</b>	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Chris Crampton  
Finance Director



Allegion (UK) Limited  
35 Rocky Lane  
Aston  
Birmingham  
B6 5RQ

10th November 2020